



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 357 759 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
29.10.2003 Bulletin 2003/44

(51) Int Cl.7: **H04N 7/52**, H04N 7/24,
H04N 7/15, H04N 7/18,
H04N 5/268

(21) Application number: **03252223.7**

(22) Date of filing: **08.04.2003**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR**
Designated Extension States:
AL LT LV MK

(72) Inventors:
• **Baker, Daniel G.**
Beaverton, Oregon 97007 (US)
• **Tucker, Thomas L.**
Aloha, Oregon 97006 (US)

(30) Priority: **15.04.2002 US 123838**


(71) Applicant: **Tektronix, Inc.**
Beaverton, OR 97077 (US)

(74) Representative: **Molyneaux, Martyn William**
Wildman, Harrold, Allen & Dixon
11th Floor, Tower 3,
Clements Inn,
London WC2A 2AZ (GB)

(54) **Automated lip sync error correction**

(57) An automated lip sync error corrector embeds a unique video source identifier ID into the video signal from each of a plurality of video sources. The unique video source ID may be in the form of vertical interval time code user bits or in the form of a watermark in an active video portion of the video signal. When one of the

video signals is selected, the embedded unique video source ID is extracted. The extracted source ID is used to access a corresponding delay value for an adjustable audio delay device to re-time a common audio signal to the selected video signal. A look-up table may be used to correlate the unique video source ID with the corresponding delay value.



EP 1 357 759 A1

Description

BACKGROUND OF THE INVENTION

[0001] The present invention relates to television technology, and more particularly to automated lip sync error correction using an embedded video source identifier to control an adjustable audio delay.

[0002] Audio-to-video (A/V) synchronization is not a new problem. Television sources (video and audio) most often start with their video and audio synchronized such that the audio signal associated with the video signal is created at the same time. One exception to this is a sporting event shot with a long focal-length lens where the audio is received at some distance with a directional microphone. Wireless cameras are sometimes used and possibly field or sub-switched with wired cameras. The wireless camera uses a compression coder/decoder that adds video delay relative to the audio and wired camera video. Since a separate microphone, not part of the wireless camera system, often picks up the audio near the source, there is an additional A/V delay when the wireless camera is switched in place of the wired camera. Additionally the video often undergoes digital processing over video frames, making it arrive even later relative to the audio. Without adding a separate audio delay, the result is the annoying television signal referred to as lip-sync error. This is particularly annoying when the video or action precedes the audio, as in the case described.

[0003] What is desired is a method for automated correction of audio-to-video (A/V) lip sync error where a separate microphone is used as the audio source for a plurality of video sources, each video source introducing a different video processing delay, in order to re-time the video and audio signals to a desired relationship.

BRIEF SUMMARY OF THE INVENTION

[0004] Accordingly the present invention provides an automated lip sync error correction using an embedded video source identifier (ID) to control an adjustable audio delay. A separate directional microphone acts as an audio source and a plurality of camera, both wired and wireless, act as video sources. The video signal from each video source has a source ID embedded in it, either in the form of vertical interval time code user bits or in the form of a watermark in the active video portion of the video signal, or both. The video sources are coupled to a camera switch that selects a particular one of the video signals. The source ID is extracted from the selected one of the video signals and used to access a look-up table that associates audio time delay to a pre-determined video source delay. The associated audio time delay is applied to an adjustable audio delay device to re-time the audio signal from the audio source with the selected one of the video signals.

[0005] The objects, advantages and other novel fea-

tures of the present invention are apparent from the following detailed description when read in conjunction with the appended claims and attached drawing.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

[0006] The Figure is a block diagram view of a television system having multiple cameras with different video delays and a separate common microphone that provides automated lip sync error correction according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0007] Referring now to the Figure an event being televised, such as a golf match in this illustration, uses a single directional microphone **12** as an audio source and a plurality of cameras **14**, **16** as video sources. The cameras **14**, **16** include both cameras directly wired to a camera switch **22** and cameras that are wirelessly coupled to the camera switch. Each camera **14**, **16** introduces a different amount of video processing delay to the video signal relative to the audio signal from the microphone **12**. In particular the wireless cameras **16** introduce a greater video delay than the corresponding wired cameras **14**. The wireless cameras **16** generally compression code the video signal, which is then transmitted via a camera antenna **17** wirelessly through a receiver antenna **18** to a receiver **20** where the video signal is compression decoded.

[0008] The broadband video signal from each camera **14**, **16** is input to a source identifier (ID) encoder **24** prior to being input to the camera switch **22**. Each source ID encoder **24** may be either a vertical interval time code (VITC) encoder or a watermark encoder, or both. The VITC encoder encodes the unique source ID for each camera **14**, **16** via VITC user bits, as is well known in the art. The watermark encoder, which is especially useful where only the active video portion of the video signal is transmitted, i.e., in digital video signal format, encodes the unique source ID for each camera **14**, **16** via a watermark embedded in the active video portion of the video signal using standard watermarking techniques, such as those described in U.S. Patent No. 6,211,919 issued April 3, 2001 entitled "Transparent Embedment of Data in a Video Signal." The camera switch **22** selects one of the source identified video signals for input to a decoder/delay device **26** together with the common audio signal.

[0009] The decoder/delay device **26** includes a source ID decoder **28** into which the selected source identified video signal is input and an adjustable audio delay device **30** into which the audio signal is input. The source ID decoder **28** extracts the source ID from the selected source identified video signal. Based on the source ID the decoder **28** accesses a look-up table **30** to select a pre-determined delay value corresponding to

the camera identified by such source ID. The delay value is output by the decoder **28** to the delay device **30** to select the delay to be applied to the audio signal. The video and audio signal outputs from the decoder **28** and delay device **30** are input to a program uplink or satellite television link (STL) **34** in synchronization with each other, i.e., the audio is re-timed with the video. The delay differences between the cameras is generally fixed and known. Therefore the software "look-up" table **32** has the known delays for each camera source ID.

[0010] Thus the present invention provides automated lip sync error correction for a television system having a separate audio source for multiple video sources by embedding a source ID into each video signal, selecting one of the video sources for output, extracting the source ID from the video signal for the selected video source, and switching in the appropriate delay for an adjustable audio delay device depending upon the extracted source ID, thereby re-timing the audio signal from the audio source with the selected video signal.

Claims

1. In a television system having a separate audio source with a plurality of video sources and a switch for selecting one of the video sources for output with the audio source, an automated lip sync error corrector comprising:

means for embedding a unique source identifier into a video signal from each of the video sources before input to the switch;
means for extracting the unique source identifier from the video signal selected by the switch for output; and
means for adjusting a delay for an audio signal from the audio source as a function of the extracted unique source identifier to re-time the audio signal with the selected video signal.

2. The corrector as recited in claim 1 wherein the adjusting means comprises:

means for accessing a delay value associated with the extracted unique source identifier; and
means for applying the delay value as the delay for the audio signal to re-time the audio signal with the selected video signal.

3. The corrector as recited in claims 1 or 2 wherein the unique source identifier comprises vertical interval time code user bits.

4. The corrector as recited in claims 1 or 2 wherein the unique source identifier comprises a watermark.

5. In a television system having a separate audio

source with a plurality of video sources and a switch for selecting one of the video sources for output with the audio source, an automated lip sync error corrector comprising:

an encoder coupled to each video source for embedding a unique source identifier into a video signal from the video source before input to the switch;

a decoder coupled to the switch for extracting the unique source identifier from the video signal selected by the switch for output; and

an adjustable audio delay device for delaying an audio signal from the audio source as a function of the extracted unique source identifier to re-time the audio signal with the selected video signal.

6. The corrector as recited in claim 5 wherein the decoder comprises a lookup table having a delay value for each unique source identifier, the delay value for the selected video signal being accessed and applied to the adjustable audio delay device to re-time the audio signal with the selected video signal.

7. The corrector as recited in claims 5 or 6 wherein each encoder comprises a vertical interval time code encoder for embedding unique vertical interval time code user bits into the video signal from the video source.

8. The corrector as recited in claims 5 or 6 wherein each encoder comprises a watermark encoder for embedding a watermark into the video signal from the video source.

9. In a television system having a separate audio source with a plurality of video sources and a switch for selecting one of the video sources for output with the audio source, an automated lip sync error correction method comprising the steps of:

embedding a unique source identifier into a video signal for each video source before input to the switch;

extracting the unique source identifier from the video signal selected by the switch for output; and

delaying an audio signal from the audio source as a function of the extracted unique source identifier to re-time the audio signal with the selected video signal.

10. The method as recited in claim 9 wherein the delaying step comprises the steps of:

accessing a look-up table for a delay value associated with the extracted unique source identifier;

tifier; and
applying the delay value to an adjustable audio
delay device to re-time the audio signal with the
selected video signal.

5

11. The method as recited in claims 9 or 10 wherein the
unique source identifier comprises vertical interval
time code user bits.

12. The method as recited in claim 11 wherein the
unique source identifier comprises a watermark.

10

15

20

25

30


35

40

45

50

55





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 25 2223

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	EP 0 845 903 A (SAMSUNG ELECTRONICS CO LTD) 3 June 1998 (1998-06-03) * abstract * * column 2, line 9 - line 13 * * column 2, line 30 - line 39 * * column 2, line 48 - line 52 * * column 3, line 46 - line 55; figures 5-8 * * column 5, line 42 - column 6, line 5 * * column 7, line 7 - line 13 * ---	1-12	H04N7/52 H04N7/24 H04N7/15 H04N7/18 H04N5/268
A	US 6 351 233 B1 (TAKENAKA HIROSHI) 26 February 2002 (2002-02-26) * abstract * * column 1, line 26 - line 33 * * column 2, line 36 - line 37 * * column 2, line 43 - line 44 * * column 2, line 53 - line 56 * * column 2, line 65 - line 67 * * column 3, line 10 - column 4, line 4 * ---	1-12	
A	EP 1 098 522 A (SONY UK LTD) 9 May 2001 (2001-05-09) * abstract * * page 2, paragraph 6 - paragraph 7 * * page 3, line 5,9,53 - last line * * page 10, line 48,51 - line 52 * * page 10, line 55 * * page 11, paragraph 107 * * page 11, paragraph 111 - paragraph 114 * ---	1-12	TECHNICAL FIELDS SEARCHED (Int.Cl.7) H04N
A	US 5 570 372 A (SHAFFER SHMUEL) 29 October 1996 (1996-10-29) * abstract * * column 2, line 31 - line 63 * * column 4, line 13 - line 40 * * column 5, line 4 - line 8 * --- -/-	1-12	
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 13 August 2003	Examiner Gries, T
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 25 2223

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	US 5 267 039 A (ELBERBAUM DAVID) 30 November 1993 (1993-11-30) * abstract *	1-12	
A	US 5 953 049 A (MANE AMIR M ET AL) 14 September 1999 (1999-09-14) * abstract * * column 1, line 43 - column 2, line 22 *	1-12	
A	US 5 818 514 A (HASKELL BARTIN GEOFFRY ET AL) 6 October 1998 (1998-10-06) * abstract *	1-12	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 13 August 2003	Examiner Gries, T
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EP FORM 1503 (8-92) (P4001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 25 2223

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-08-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0845903	A	03-06-1998	KR 238668 B1	15-01-2000
			CN 1184313 A ,B	10-06-1998
			EP 0845903 A2	03-06-1998
			JP 10164514 A	19-06-1998
			US 2001012441 A1	09-08-2001

US 6351233	B1	26-02-2002	JP 2001136503 A	18-05-2001

EP 1098522	A	09-05-2001	BR 0005253 A	19-06-2001
			EP 1102276 A1	23-05-2001
			EP 1102277 A1	23-05-2001
			EP 1098522 A1	09-05-2001
			EP 1102271 A1	23-05-2001
			GB 2356080 A	09-05-2001
			JP 2001184802 A	06-07-2001
			JP 2001195868 A	19-07-2001
			JP 2001216763 A	10-08-2001
			JP 2001216726 A	10-08-2001

US 5570372	A	29-10-1996	CA 2236907 C	11-09-2001
			DE 69605948 D1	03-02-2000
			DE 69605948 T2	18-05-2000
			EP 0882359 A2	09-12-1998
			JP 10512736 T	02-12-1998
			WO 9717798 A2	15-05-1997

US 5267039	A	30-11-1993	NONE	

US 5953049	A	14-09-1999	NONE	

US 5818514	A	06-10-1998	NONE	
